

SERIA FR G-L-P DEC



seria G - L - P - K
Amortyzator hydrauliczny



DANE TECHNICZNE								
ZASIĘG RAMIENIA	DEC FR 300 G	DEC FR 380 G	DEC FR 450 L	DEC FR 500 L	DEC FR 500 P	DEC FR 550 P	DEC FR 650 P	
A (mm.)	1400	1600	1600	1800	2050	2050	2300	
B (mm.)	3000	3800	4500	5000	5000	5500	6500	
C (mm.)	1200		1400	1600	1700	1700	2100	
D (mm.)	3200	4000	4500	5000	5000	5400	6200	
E (mm.)	1600	2200	2700	3500	3600	4100	5200	
Ciężar (kg.)	380	400	630	700	1000	1050	1100	
SYSTEM HYDRAULICZNY	DEC FR 300 G	DEC FR 380 G	DEC FR 450 L	DEC FR 500 L	DEC FR 500 P	DEC FR 550 P	DEC FR 650 P	
Pojemność zbiornika oleju (l)	80		110		200			
Olej hydrauliczny (typ)	ISO - L - HM 68		ISO - L - HM 68		ISO - L - HM 68			
GŁOWICA TNĄCA	DEC FR 300 G	DEC FR 380 G	DEC FR 450 L	DEC FR 500 L	DEC FR 500 P	DEC FR 550 P	DEC FR 650 P	
Szerokość robocza (mm.)	600-800		800-1000		1000-1300			
Ciężar (kg.)	70-80	70-100	100-120		180-200			
Prędkość obrotowa wału (obr./min.)	3000		3000		3000			
Moc wału (KM)	29		29 - 47		57			
WYMAGANIA TRAKTORA	DEC FR 300 G	DEC FR 380 G	DEC FR 450 L	DEC FR 500 L	DEC FR 500 P	DEC FR 550 P	DEC FR 650 P	
Min. moc traktora (KM)	70	80	90		180	180	200	
Min. ciężar traktora (kg.)	3500	3800	4000	4200	5800	6200	6500	
Prędkość obrotowa PTO (obr./min.)	540		540		540			