

SERIA Green Line

KOPARKI MONTOWANE NA TUZ TRAKTORA



Zastosowanie urządzenia blokującego.



Mod. L



Mod. B



Mod. BA

DANE TECHNICZNE

ZASIĘG RAMIENIA KOPARKI		B / BA 13	B / BA 15	L 13	L 15	L 16
A	(mm.)	1300	1500	1300	1500	1500
B	(mm.)	1200	1600	1200	1600	1600
C	(mm.)	1900	2300	1900	2300	2300
D Promień pracy	(mm.)	2000	2500	2000	2500	2500
Szerokość ramy transportowej	(mm.)			1000	1000	1200
Siła skrawania łyżką	(kg.)	1500	1800	1500	1800	1800
Kąt obrotu ramienia		180°				
Wydatek pompy	(l./min)	13	15	13	15	15
Ciśnienie robocze	(Bar)	180				
Pojemność zbiornika	(l.)	15	25	25	25	25
Łyżka koparki	(mm.)	250÷400				
Ciężar z łyżką	(kg.)	250	290	280	300	320
Min. ciężar traktora	(kg.)	650	750	750	800	850
Min. moc traktora	(KM)	13	15	13	15	15

Mod. B

Min. 920 mm.



Max. 1200 mm.

Mod. BA

Min. 1250 mm.



Max. 2000 mm.

Mod. L

