


SERIA Dig Dig

KOPARKI MONTOWANE NA TUZ TRAKTORA



DANE TECHNICZNE

ZASIĘG RAMIENIA KOPARKI		70 TIX	75 TIX	80 TIX	85 TIX	90 TIX	100 TIX
A	(mm.)	2700	2800	3000	3100	3500	4200
B	(mm.)	2500	2500	2700	2700	3100	3850
C	(mm.)	3500	3500	3700	3700	4200	4950
D Promień pracy	(mm.)	3500	3550	3800	3850	4000	5100
Szerokość ramy transportowej	(mm.)	1800	2000	1800	2000	2000	2000
Siła skrawania łyżką	(kg.)	2800	2800	2900	2900	3550	5600
Kąt obrotu ramienia		180°				180°	
Wydatek pompy	(l /min)	30	30	38	38	57	78
Ciśnienie robocze	(Bar)	180				180	
Pojemność zbiornika	(l)	50	50	50	50	70	70
Łyżka koparki	(mm.)	250÷400	250÷400	250÷400	250÷400	250÷800	250÷800
Ciężar z łyżką	(Kg.)	770	800	860	890	1200	1700
Min. ciężar traktora	(kg.)	2500	2600	2800	2900	4000	6000
Min. moc traktora	(KM)	60	60	70	70	100	120

Niezależny stabilizator.

